

SPECIFICATION SHEET

BrightLink[®] 725Wi WXGA 3LCD Interactive Laser Display



Product shown with mount, sold separately.

Enhance classroom engagement with this bright, easy-to-read WXGA interactive display.

Ultra bright - 4,000 lumens of color/white brightness¹

Large, true-to-life images — WXGA display; projects high-quality, easy-to-read 16:10 displays up to 100" diagonal

Laser light source life — virtually maintenance-free 20,000-hour laser light source with no lamps to replace²

Lowest cost per square inch vs. interactive panels³ - up to 85 percent more interactive space vs. 75" flat panel

Time-saving installation — automatic image alignment and pen calibration makes installation easier than ever before

Dual, pen-enabled interactivity — allows up to eight users to collaborate at once when used with new or existing touch modules

PC-free digital whiteboard — draw, save, print and email without a PC; also share whiteboard content from other networked BrightLink 1480 series projectors

Built-in 5GHz wireless — supports wireless interactivity via Miracast[®] and wireless displays; display and share content simultaneously to/from up to 50 connected devices⁴ via Epson iProjection[™] software

Easy replacement of BrightLink 595Wi/695Wi series — using existing cables, mount and touch module

SMART Learning Suite — includes 1-year subscription and support for SMART Notebook[®], SMART amp[™], SMART lab[™], SMART Learning Suite Online and more





Education



BrightLink® 725Wi WXGA 3LCD Interactive Laser Display

Specifications

Projection System Epson® 3LCD, 3-chip technology Projection Method Front/rear/wall mount/table mount Driving Method Epson Poly-silicon TFT Active Matrix Pixel Number 1,024,000 dots (1280 x 800) x 3 Color Brightness¹ Color Light Output: 4,000 lumens White Brightness¹ White Light Output: 4,000 lumens Aspect Ratio 16:10 Native Resolution 1280 x 800 (WXGA) Light Source² Laser Light Source Life² Up to 20,000 hours Size (Projected) (16:10) 100" Keystone Correction (Manual) Horizontal: ± 3 degrees; Vertical: ± 3 degree USB Plug 'n Play Mac OS® 10.8/10.9/10.10/10.11/10.12/ 10.13/10.14/macOS 10.15.x USB Plug 'n Play for Windows® Windows 7/Windows 8/ Windows 10 Contrast Ratio Up to 2,500,000:1 Color Reproduction Up to 1.07 billion colors

Wireless Specifications

Supported Security Mode OPEN, WPA2/WPA3-PSK, WPA2/WPA3-EAP Supported EAP Type PEAP, PEAP-TLS, EAP-TLS, EAP-Fast Supported Speeds: IEEE 802.11b: 11 Mbps* (2.4 GHz) IEEE 802.11g: 54 Mbps* (2.4 GHz) IEEE 802.11n: 72.2 Mbps* (2.4 GHz) IEEE 802.11a: 54 Mbps* (5 GHz) IEEE 802.11n: 150 Mbps* (5 GHz) IEEE 802.11ac: 325 Mbps* (5 GHz) *Maximum speed and range is achievable when used with the same Enhanced Mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors

Projection Lens

Type Manual focus F-Number 1.6 Focal Length 3.7 mm Throw Ratio Range 0.28 - 0.37 (16:10) Zoom Ratio Digital zoom 1.0 – 1.35x

Other

Speaker 16 W monaural Operating Temperature 41 $^\circ$ to 104 $^\circ$ F (0 $^\circ$ to 40 $^\circ$ C) Power Supply Voltage 100 – 240 V $\pm10\%$, 50/60 Hz Power Consumption Quiet Mode: 206 W Normal Mode: 267 W Standby (Communication On): 2.0 W Standby (Communication Off): 0.5 W **Fan Noise** Quiet Mode: 26 dB Normal Mode: 36 dB Security Kensington lock provision, security anchor bar, password-protection function

Interfaces

HDMI®: 3 Composite Video: 1x RCA (Yellow) Audio In: 3x Mini stereo Audio Out: 1x Mini stereo Microphone in: 1x Mini stereo USB Connector: 2x Type A (1x USB memory/document camera; 1x Wireless only) USB Connector: 2x Type B (USB display with audio and interactivity) Serial: 1x RS-232c Monitor Out/Computer: 1x D-sub 15 pin Computer: 1x D-sub 15 pin Integrated Wireless LAN: 802.11 b/g/n/ac Interactive Synchronization Mini stereo In Interactive Synchronization Mini stereo Out **Touch Unit Connection Port**

Interactivity

Interactive Technology Infrared, 850 nm Interactive Area (Image Size) 100" diagonal (16:10) Interactive Modes Computer Interactivity, PC-free and Whiteboard Annotation Mode, Pen: Dual User, Finger Touch: Up to 6 points of touch PC-free Annotation Two pens and two fingers Interactive Tools Epson Easy Interactive Tools, Two pens and

six finders PC Interactive Sources USB, HDMI, Computer 1, Computer

2, LAN, Miracast PC-free Annotation Devices Document Cameras, DVD/ Blu-

ray Disc[®] player, iPod[®]/iPad[®] devices, Chromebooks Calibration Method Automatic or Manual

Interactive Connectivity USB cable for non-networked LAN Interactive Software Requirements

Epson Easy Interactive Driver (required for Mac) Mac®: Mac OS X® 10.12/10.13/10.14/macOS 10.15.x

Epson Easy Interactive Tools for Windows and Mac System Compatibility Microsoft® Windows Vista, Windows Vista SP1, Windows Vista SP2 (All editions except for Starter), Windows 8/8.1, Windows 10, Windows 7 SP1 (All editions except for Starter), Mac OS 10.11/10.12/10.13/10.14/ macOS 10.15.x

Gestures Requires Windows 7 or later, or Mac OS 10.12 or later

SMART Learning Suite System Requirements

Supported Operating Systems Windows 7 SP1, Windows 8/8.1, Windows 10, Mac OS X 10.12, 10.13, 10.14, 10.15 Minimum Processor Intel Core 2 Duo (Mac)

Intel Core m3 (Windows) Minimum RAM 4 GB (8 GB for UHD displays) Minimum Hard Disk Space 4.7 GB (Windows); 2.3 GB (Mac)

Dimensions (W x D x H)

Excluding Feet 14.1" x 15.6" x 5.25 Weight 12.7 lb



Additional USB-A port on side of projector

Remote Control

Features Computer, HDMI, USB, LAN, Source Search, Power, Aspect, Color Mode, Volume, E-Zoom, A/V Mute, Freeze, Menu, Auto, Enter, ESC, User, ID, Default, Home, Split **Operating Angle**

Rear: Right/left: -55 to +55 degrees, Upper/lower: +75 to +15

degrees Front: Right/left: -30 to +30 degrees, Upper/lower: 0 to +60

degrees Operating Distance 19.7 ft (6 m)

Eco Features

Energy-efficient 3LCD light engine RoHS compliant

Recyclable product5 Epson America, Inc. is a SmartWay® Transport Partner

Support

Service Programs 3-year projector limited warranty, Epson Road Service Program, dedicated toll-free support

What's in the Box

BrightLink 725Wi ultra short-throw interactive projector, Quick Start Guide, 6' power cable, 16' USB A/B cable, projector remote control, two (2) interactive pens, four (4) soft pen tips, two (2) hard pen tips, pen tray, two (2) AA batteries (for interactive pens) plus battery charger, two (2) AA batteries (for remote), projector feet, corner markers, magnets for corner markers, password protect sticker, SMART Learning Suite redemption code

Ordering Information

BrightLink 725Wi	V11H998520
Air Filter	V13H134A60
Ultra Short-throw Wall Mount (ELPMB62)	V12HA06A05
Interactive Touch Module	V12H007A23
PowerLite Pilot 3 (ELPCB03)	V12H927020
Active Speakers (ELPSP02)	V12H467020
Wireless 802.11b/g/n LAN Unit (ELPAP11)	V12H005A02
100" Whiteboard (16:10)	V12H831000
Interactive Pen A (orange)	V12H773010
Interactive Pen B (blue)	V12H774010
Replacement Pen Tips (hard/Teflon®	V12H775010
Replacement Pen Tips (soft/felt)	V12H776010
DC-07 Document Camera	V12H759020
DC-13 Document Camera	V12H757020
DC-21 Document Camera	V12H758020

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.1 **2** No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. 1 **3** Versus comparable interactive flat panel displays measuring 65-inches and above. PMA Research data for 2020 10, North America. I **4** For wireless functionality, including via the Epson Projector nap, the projector nap, the rojector mode on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson Projector nap, then Epson Projector nap, then Epson Projector nap, the Epson Projector nap, the Epson Projector app, the US. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

Better Products for a Better Future eco.epson.com

Epson America, Inc.

Epson Canada Limited





Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. BrightLink and PrivateLine are registered trademarks and Pilot is a trademark of Epson America, Inc. Miracast[®] is a registered trademark of Wi-Fi Alliance[®]. Mac, macOS and OS X are trademarks of Apple Inc., registered in the U.S. and other countries. Microsoft Windows and Windows Vista are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2020 Epson America, Inc. CPD-59392 07/20

SmartWav Transport Partne

3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Contact: